



LAUKO PROŽEKTORIAI serija ADMIRAL



KODAS	AD21B-40	AD21B-60	AD21C-80	AD21C-100	AD21C-120	AD21D-150	AD21D-180	AD21E-240
Šviesos spektras (CCT)	4000K (standartas) / 3000K 5000K 5700K (užsakoma)							
Darbinė temperatūra	-40°C -- +50°C							
Spalvų atgavos indeksas	Ra≥70							
Galia	40W	60W	80W	100W	120W	150W	180W	240W
Svoris, kg	2.8		3.7			6.1		6.8
Matmenys LxBxH, mm	260x230x220		275x360x230			375x385x250		450x385x285
Jėgos faktorius (PF)	0.96							
Šviestuvo efektyvumas	150-175 lm/W							
Ryškus	6520 lm	9000 lm	14000 lm	17000 lm	19560 lm	25500 lm	29340 lm	39120 lm
Apsaugos klasė IP / IK	IP68 diodų bloko; IP67 maitinimo šaltinis / IK08							
Šviesos sklaidimo kampas	25° / 40° / 60° / 90° / 40x90° / Eliptinė							
Valdymas (Dimeriavimas)	0~10Vdc, PWM, Timer dimming. Dim-to-off							
Tarnavimo laikas	L80B10 80000 h (Ts-25 °C)							
Maitinimo šaltinis / Šviesos diodų gamintojas	MOSO / INVENTRONICS / SOSEN ; LUMILEDS 5050							
Korpuso medžiaga	Aliuminis (spalvos pilka/juoda) + Optika / Pildomas grūdintas stikliukas (užsakoma)							

