



PRAMONINIS LED ŠVIESTUVAS

serija Hunter



5 Years Warranty



KODAS	Hunter-L300	Hunter-L600	Hunter-L900	Hunter-L1200	Hunter-L1200	Hunter-L1500	Hunter-L1500
Šviesos spektras (CCT)	4000K (standartas) / 3000K 5000K 5700K 6500K (užsakoma)						
Darbinė temperatūra	-35°C -- +50°C						
Spalvų atgavos indeksas (CRI)	Ra≥80						
Galia	40-60 W	80-120 W	150-180 W	200W	240W	250W	300W
Svoris, kg	2.2	3.4	4.5	5.8	5.8	7.2	7.2
Matmenys LxWxH, mm	385x170x150	690x170x150	990x170x150	1290x170x150	1290x170x150	1590x170x150	1590x170x150
Jėgos faktorius (PF)	0.95						
Šviestuvo efektyvumas	170-185 lm/W						
Apsaugos klasė IP / IK / UGR	IP65 / IK10 / UGR≤21						
Šviesos sklaidimo kampas	60x90° / 90x120° / 120°						
Valdymas (Dimeriavimas)	Non-Dimming/0-10V Dimming/DALI						
Tarnavimo laikas	L90B10 100000 h (Ts-85 °C)						
Maitinimo šaltinis / Šviesos diodų gamintojas	Moso/Sosen/Philips/Meanwell/ZH ; žymiausi pasauliniai gamintojai						
Korpuso medžiaga	Aliuminis + optika						

