



PRAMONINIS LED ŠVIESTUVAS
serija MUSKETEER



Low glare
UGR<19



KODAS	MUSK-50	MUSK-100	MUSK-150	MUSK-200	MUSK-250	MUSK-300	MUSK-400
Šviesos spektras (CCT)	4000K (standartas) / 3000K 5000K 5700K 6500K (užsakoma)						
Darbinė temperatūra	-40°C -- +50°C						
Spalvų atgavos indeksas (CRI)	Ra≥70, Ra≥80						
Galia	50W	100W	150W	200W	250W	300W	400W
Svoris, kg	2.5	3.7	4.7	5.7	9.5	9.7	11.4
Matmenys LxBxH, mm	350x126x172	634x126x172	917x126x172	1200x126x172	958x312x172	958x312x172	1241x312x172
Jėgos faktorius (PF)	0.95						
Šviestuvo efektyvumas	130 lm/W						
Apsaugos klasė IP / IK	SAA, CE, RoHS, IP65 / IK10						
Šviesos sklaidimo kampas	100°						
Valdymas (Dimeriavimas) / Avarinis	DALI/ 0-10v/ triac dimming /motion sensor / Zigbee / avarinio maitinimo galimybė						
Tarnavimo laikas	L70B20 100000 h (Ts-25 °C)						
Maitinimo šaltinis / Šviesos diodų gamintojas	Meanwell ; Phillips lumiled/CREE 3030 chip						
Korpuso medžiaga	Grafenas + optika						

