



## Technical information

<b>Power:</b>	9W
<b>Color temperature:</b>	3000K-4000K-6500K
<b>Product size:</b>	Ø120mmx H25mm
<b>Cut size:</b>	90-110 mm
<b>Operating temperature:</b>	-25 +40 C °
<b>Voltage:</b>	220-240 V AC
<b>Frequency:</b>	50/60 Hz
<b>Beam angle:</b>	120 °
<b>CRI:</b>	≥80
<b>PF:</b>	≥0.50
<b>IP:</b>	IP20
<b>Color body:</b>	white
<b>Usage:</b>	inside
<b>Warranty:</b>	2 years





## Technical information

<b>Power:</b>	18W
<b>Color temperature:</b>	3000K-4000K-6500K
<b>Product size:</b>	Ø170mmx H25mm
<b>Cut size:</b>	140-160 mm
<b>Operating temperature:</b>	-25 +40 C°
<b>Voltage:</b>	220-240 V AC
<b>Frequency:</b>	50/60 Hz
<b>Beam angle:</b>	120°
<b>CRI:</b>	≥80
<b>PF:</b>	≥0.50
<b>IP:</b>	IP20
<b>Color body:</b>	white
<b>Usage:</b>	inside
<b>Warranty:</b>	2 years





## Technical information

<b>Power:</b>	24W
<b>Color temperature:</b>	3000K-4000K-6500K
<b>Product size:</b>	Ø220mmx H25mm
<b>Cut size:</b>	190-210 mm
<b>Operating temperature:</b>	-25 +40 C°
<b>Voltage:</b>	220-240 V AC
<b>Frequency:</b>	50/60 Hz
<b>Beam angle:</b>	120°
<b>CRI:</b>	≥80
<b>PF:</b>	≥0.50
<b>IP:</b>	IP20
<b>Color body:</b>	white
<b>Usage:</b>	inside
<b>Warranty:</b>	2 years

