


LED Tri-proof Light

Zoro-L1200-35W-A2

- An IP65 waterproof LED light.
- 130lm/W
- Integrates PC cover with light diffusing agent and colored PC housing.
- Housing caps sealed by silicon rubber gasket.
- Adopt male and female quick connector, making the wiring easier.
- Can be applied in wet interior, dusty place and outdoor places such as Cellars Sheds Plant rooms Warehouses Open and closed parking areas Workstations Corridors etc.



130lm/W



Specification | Technical & Product Data:

LED TYPE	SMD 2835
Wattage	35 W
Frequency	50-60 HZ
Power Factor	>0.9
Light color	Natural white
Color Temperature	4000 K
SDCM	<5
Light efficiency	typ. 130 lm/W
Luminous flux	typ. 4550 lm
CRI	>80
Size	1191 * 70 * 69mm
Lifespan L80/B10	50000 hrs at 25 C
IP rate	IP65
ON/Off cycles	>30000
Working conditions	-20 C - 45 C
Material	PC
Body Color	White
Certification	CE ERP RoHS ENEC
Type of light source	◀ E
Warranty	5 Years


IP65 IK08



LED Tri-proof Light

Zoro-L1200-35W-A3

- An IP65 waterproof LED light.
- 130lm/W
- Integrates PC cover with light diffusing agent and colored PC housing.
- Housing caps sealed by silicon rubber gasket.
- Adopt male and female quick connector, making the wiring easier.
- Can be applied in wet interior, dusty place and outdoor places such as Cellars Sheds Plant rooms Warehouses Open and closed parking areas Workstations Corridors etc.



130lm/W



Specification | Technical & Product Data:

LED TYPE	SMD 2835
Wattage	35 W
Frequency	50-60 HZ
Power Factor	>0.9
Light color	Natural white
Color Temperature	4000 K
SDCM	<5
Light efficiency	typ. 130 lm/W
Luminous flux	typ. 4550 lm
CRI	>80
Size	1191 * 70 * 69mm
Lifespan L80/B10	50000 hrs at 25 C
IP rate	IP65
ON/O ffcycles	>30000
Working conditions	-20 C - 45 C
Material	PC
Body Color	White
Certification	CE ERP RoHS ENEC
Type of light source	◀ E
Warranty	5 Years


IP65 IK08



LED Tri-proof Light

Zoro-L1500-50W-A2

- An IP65 waterproof LED light.
- 130lm/W
- Integrates PC cover with light diffusing agent and colored PC housing.
- Housing caps sealed by silicon rubber gasket.
- Adopt male and female quick connector, making the wiring easier.
- Can be applied in wet interior, dusty place and outdoor places such as Cellars Sheds Plant rooms Warehouses Open and closed parking areas Workstations Corridors etc.



130lm/W



Specification | Technical & Product Data:

LED TYPE	SMD 2835
Wattage	50 W
Frequency	50-60 HZ
Power Factor	>0.9
Light color	Natural white
Color Temperature	4000 K
SDCM	<5
Light efficiency	typ. 130 lm/W
Luminous flux	typ. 6500 lm
CRI	>80
Size	1473 * 70 * 69mm
Lifespan L80/B10	50000 hrs at 25 C
IP rate	IP65
ON/O ffcycles	>30000
Working conditions	-20 C - 45 C
Material	PC
Body Color	White
Certification	CE ERP RoHS ENEC
Type of light source	◀ E
Warranty	5 Years


IP65 IK08



LED Tri-proof Light

Zoro-L1500-50W-A3

- An IP65 waterproof LED light.
- 130lm/W
- Integrates PC cover with light diffusing agent and colored PC housing.
- Housing caps sealed by silicon rubber gasket.
- Adopt male and female quick connector, making the wiring easier.
- Can be applied in wet interior, dusty place and outdoor places such as Cellars Sheds Plant rooms Warehouses Open and closed parking areas Workstations Corridors etc.



130lm/W



Specification | Technical & Product Data:

LED TYPE	SMD 2835
Wattage	50 W
Frequency	50-60 HZ
Power Factor	>0.9
Light color	Natural white
Color Temperature	4000 K
SDCM	<5
Light efficiency	typ. 130 lm/W
Luminous flux	typ. 6500 lm
CRI	>80
Size	1473 * 70 * 69mm
Lifespan L80/B10	50000 hrs at 25 C
IP rate	IP65
ON/O ffcycles	>30000
Working conditions	-20 C - 45 C
Material	PC
Body Color	White
Certification	CE ERP RoHS ENEC
Type of light source	◀ E
Warranty	5 Years

IP65 IK08

